	P	0	N	E		2
LIGHT	UΡ	THE	W	0	R	D



Model	POWER 10K5	POWER 11K6				
Performance						
Nominal Voltage	51.2 Vdc					
Nominal Capacity	205 Ah	228 Ah				
Battery Energy	10.5 kWh	11.6 kWh				
Charge Current	120 A					
Charge Power	6144 W					
Discharge Current	170 A					
Discharge Power	8704 W					
Short Circuit Current	540 A					

	Communica
Display	
Communication	

	General Specif
Dimension (W×D×H mm)	
Weight (kg)	
Installation	I
Working Temperature	
Operating / Storage Humidity	
Max Operating Altitude	
IP Rating	
Cell Technology	LiFe
Cycle Life	6000 Cycles
Scalability	Γ

Standard	Compliance	(more

Certificates

Product Ordering Part

POWER 10K5 Battery (Cable / wall mount included) POWER 11K6 Battery (Cable / wall mount included)



Grade A LiFePO₄Cell

Compatible with Major PCS Brand

Scalable From 10.5

To 730.8 kWh

ation

Color touchscreen

CAN, RS485, RS232

ification

465 x 186 x 695 mm

83.5 kg

Floor Stand or Wall Mount

-20°C-60°C

≤95% RH

≤2000 m

IP20

FePO4, Lithium Iron Phosphate

es @ 80% DoD / 25°C / 0.5C, 60% EOL

Max 63 batteries in parallel

re available upon request)

CE, UN38.3

Ordering And Deliverable Part