



<b>Model</b>	POWER 2560-12.8V
--------------	------------------

Performance	
Nominal Ratings	12.8 V, 200 Ah, 2.56 kWh
Bulk Charge V	14 V
Float Charge V	13.8 V
Low Voltage	12.8 V
Cutoff Voltage	11.6 V
Charge Current	100 A
Discharge Current	200 A
Short Circuit Current	≈1000 A

General Specification	
Dimension (WxDxH mm)	502 x 186 x 241 mm
Weight (kg)	19.6 kg
Working Temperature	-20°C - 60°C
Operating / Storage	≤95% RH
Max Operating Altitude	≤2000 m
IP Rating	IP54
Cell Technology	LiFePO <sub>4</sub> , Lithium Iron Phosphate
Cycle Life	6000 Cycles @ 80% DoD / 25°C / 0.5C, 60% EOL
Scalability	Max 4 batteries in series Max 4 batteries in parallel

Standard Compliance (more available upon request)	
Certificates	CE, UN38.3

Ordering and Deliverable Part	
Product Ordering Part	POWER 2560-12.8V Battery

**RELIABLE**  
Grade A  
LiFePO<sub>4</sub> Cell

**SCALABLE**  
Scalable From 2.56  
To 20.48 kWh